DoT project area pavement condition ratings

| Project | Project Limits | | Lane Miles | PCI* VALUES | Treatment |
|---------|----------------|-----------|------------|-------------|----------------|
| 21st | Monroe | Adams | 0.66 | 16,14,22,23 | Reconstruction |
| 20th | Monroe | Adams | 0.63 | 33,33,5 | Reconstruction |
| 19th | Monroe | Jefferson | 0.20 | 17 | Reconstruction |
| 18th | Monroe | Adams | 0.66 | 34,42,34 | Reconstruction |
| 16th | Monroe | Adams | 1.00 | 30,4,9 | Reconstruction |
| 15th | Monroe | Jefferson | 0.24 | 10 | Reconstruction |
| 15th | Madison | Adams | 0.24 | 11 | Reconstruction |
| 13th | Monroe | Adams | 0.60 | 15,13,11 | Reconstruction |

| PCI Value | Meaning |
|-----------|--------------|
| 86100 | Good |
| 7185 | Satisfactory |
| 5670 | Fair |
| 4155 | Poor |
| 2640 | Very Poor |
| 1125 | Serious |
| 010 | Failed |

| | | | | PCR** VALUES | |
|-------|----------|----------|------|--------------|-------------|
| Adams | Woodruff | Michigan | 2.30 | 56 | Resurfacing |
| 17th | Monroe | Adams | 1.21 | 78 | Resurfacing |
| 14th | Monroe | Adams | 1.00 | 91,71 | Resurfacing |

| PCR Value | Meaning |
|-----------|--------------|
| 90-100 | Very Good |
| 75-90 | Good |
| 65-75 | Fair |
| 55-65 | Fair to Poor |
| 40-55 | Poor |
| 0-49 | Very Poor |

^{*} PCI (Pavement Condition Index) measured by Engineering and Research International, Inc.

^{**}PCR (Pavement Condition Rating) measured by Ohio Department of Transportation